



**Park
Thermal
International (1996) Corporation**

62 Todd Road, Georgetown, Ontario L7G 4R7

Tel: (905) 877-5254 Fax: (905) 877-6205

Toll Free: (877) 834-4328

Email: jmistry@parkthermal.com

www.parkthermal.com

Equipment Description

Item # 3680

Manufacturer:	NEWAGE
Type:	ROCKMATE PORTABLE HARDNESS TESTER
Serial Number:	753
Model Number:	MR-DR
Tester Dimensions:	5 ¼" High x 1 ¾" wide x 2 ½" long (test head); 3" High x 5" Wide x 9" long (electronics)
Test Time:	2 to 3 seconds
Tester Weight:	1 ½ lbs (head only)
Scales:	Rockwell C. B. A. E, Vickers, Brinell HB30, HB5
Minimum Thickness:	HRC60 – 0.003"; HRC25 – 0.011"; HRB85 – 0.016"; HRB33 – 0.024"
Test Accuracy:	±1 point Rockwell C; ±1.5 points Rockwell B
Surface Preparation:	110 RA or 125 RMS or better recommended
General:	Complete system includes Tester and battery powered digital readout unit, AC/DC power converter, belt clip attachment, test blocks for Rockwell C and B, snap-on anvil base for flat and small diameter round surfaces, adjustable base for testing non-regular surfaces; base for testing larger rounds; 2 ½" long x 1 ¼" diameter extension for testing recessed areas, carrying case, pocket hardness conversion chart, instructions.

NOTE: equipment is sold "AS IS, WHERE IS" and buyer shall indemnify seller against and hold seller harmless from any and all claims, actions and damages arising out of the possession, operation, condition or use of the equipment.

Seller suggests that you contact the manufacture for important information pertaining to safety and proper use and operation of the above equipment. For safety reasons, we request that you do not place the equipment into service until you have received current safety instructions from the manufacturer.